

## **20-Handheld Device Static USB Charging Cabinet** - Desk Mounted for smartphones, mobile phones and other devices up to 7" – Horizontal

- The Lyte 20 Single Door Mobile Phone USB charges 20 devices up to 7" screen size smartphones, mobile phones and handheld USB devices (including protective cases) via a 20 port USB A Hub.
- This unit delivers high-speed charge at the optimum rate.
- **This unit is fast and efficient**, delivering fast speed charging at the optimum rate, 2.1amps maximum per port.
- Equivalent to 20 x 12W USB A Charging Ports saving you space and power consumption, replacing extension cables and power sockets with one cable into the wall
- It never overcharges as it detects when the device battery is full providing trickle charge.
- **Provides maximum security & safety** with a dual point locking system and separate lockable power compartment.
- With Support for Life with Lifetime Warranty (5 years electrical), shipped fully assembled.



	Code/SKU	Number of devices can hold	Unit Dimensions	Device Compartment Size
Lyte 20 Single Door Mobile Phone USB	LYT20SDMPUSBBL	20	<b>W</b> 315 x <b>D</b> 440 x <b>H</b> 360 mm 12.4" x 17.3" x 14.2"	<b>W</b> 220 x <b>D</b> 205 x <b>T</b> 30mm 8.7" x 8.1" x 1.2"
IMPORTANT NOTE: CHECK ACTUAL DEVICE SIZE, INCLUDING POWER CABLE FOR COMPATIBILITY WITH DEVICE COMPARTMENT SIZE.  IF IN DOUBT PLEASE CONTACT LAPCABBY FOR CONFIRMATION				
Materials	18mm MFC and 1.6mm powder coated steel			
Safety	All products are tested to the highest standard Europe: EN 62368-1:2014  Safety testing is a high priority to LapCabby. We don't release any products unless the unit has been completely certified including electrics, materials, construction and components. Leading safety testing house we test the normal operating conditions of the product but also for faults, misuse, temperature, fire risk, electric shock and injury			
Testing certifications	Safety tested to the highes	tt level UK CA	: E	







Handheld Devices

















## LapCabby<sub>®</sub>



Inset door handles.



Lock supplied with 6 plate lever activation system.



Non-marking feet.





Well placed side vents.



1.6mm grey steel fixed shelves with ventilations.



11111 11111

Isolated power compartment for electrical safety.



IEC power cable into the mains.

